

Dzus Springs

5/8" Spring		Rivet Size 3/32"		Recommended Deflection .019" - .039"	
Material	Part #	Spring Height	Fastener Length >	0.250	0.400
Stainless Steel	PANSSS3175	.175	Material Thickness Range >	.044 - .064	.194 - .214
Stainless Steel	PANSSS3225	.225	Material Thickness Range >	.094 - .114	.244 - .264

3/4" Spring		Rivet Size 3/32"		Recommended Deflection .019" - .039"	
Material	Part #	Spring Height	Fastener Length >	0.250	0.400
Stainless Steel	PANSSS4200	.200	Material Thickness Range >	.069 - .089	.219 - .239
Stainless Steel	PANSSS4250	.250	Material Thickness Range >	.019 - .039	.169 - .189

1" Spring		Rivet Size 1/8"		Recommended Deflection .023" - .056"					
Material	Part #	Spring Height	Fastener Length >	0.400	0.450	0.500	0.550	0.600	0.650
Cadmium Plated Steel	PANS5200	.200	Material Thickness Range >	.223 - .258	.273 - .308	.323 - .358	.373 - .408	.425 - .458	.473 - .508
Stainless Steel	PANSSS5200								
Cadmium Plated Steel	PANS5225	.225	Material Thickness Range >	.198 - .233	.248 - .283	.298 - .333	.348 - .383	.398 - .433	.448 - .483
Stainless Steel	PANSSS5225								
Cadmium Plated Steel	PANS5250	.250	Material Thickness Range >	.173 - .208	.223 - .258	.273 - .308	.323 - .358	.373 - .408	.423 - .458
Stainless Steel	PANSSS5250								
Cadmium Plated Steel	PANS5275	.275	Material Thickness Range >	.148 - .183	.198 - .233	.248 - .283	.298 - .333	.348 - .383	.398 - .433
Stainless Steel	PANSSS5275								
Cadmium Plated Steel	PANS5300	.300	Material Thickness Range >	.123 - .158	.173 - .208	.223 - .258	.273 - .308	.323 - .358	.373 - .408
Stainless Steel	PANSSS5300								
Cadmium Plated Steel	PANS5325	.325	Material Thickness Range >	.098 - .133	.148 - .183	.198 - .233	.248 - .283	.298 - .333	.348 - .383
Stainless Steel	PANSSS5325								
Cadmium Plated Steel	PANS5350	.350	Material Thickness Range >	.073 - .108	.123 - .158	.173 - .208	.223 - .258	.273 - .308	.323 - .358
Stainless Steel	PANSSS5350								
Cadmium Plated Steel	PANS5375	.375	Material Thickness Range >	.048 - .083	.098 - .133	.148 - .183	.198 - .233	.248 - .283	.298 - .333
Stainless Steel	PANSSS5375								

1-3/8" Spring		Rivet Size 1/8"		Recommended Deflection .030" - .073"					
Material	Part #	Spring Height	Fastener Length >	0.400	0.450	0.500	0.550	0.600	0.650
Cadmium Plated Steel	PANS6225	.225	Material Thickness Range >	.205 - .248	.255 - .298	.305 - .348	.355 - .398	.405 - .448	.455 - .498
Stainless Steel	PANSSS6225								
Cadmium Plated Steel	PANS6250	.250	Material Thickness Range >	.180 - .233	.230 - .273	.280 - .323	.330 - .373	.380 - .423	.430 - .473
Stainless Steel	PANSSS6250								
Cadmium Plated Steel	PANS6275	.275	Material Thickness Range >	.155 - .198	.205 - .248	.255 - .298	.305 - .348	.355 - .398	.405 - .448
Stainless Steel	PANSSS6275								
Cadmium Plated Steel	PANS6300	.300	Material Thickness Range >	.130 - .173	.180 - .223	.230 - .273	.280 - .323	.330 - .373	.380 - .423
Stainless Steel	PANSSS6300								
Cadmium Plated Steel	PANS6325	.325	Material Thickness Range >	.105 - .148	.155 - .198	.205 - .248	.255 - .298	.305 - .348	.355 - .398
Stainless Steel	PANSSS6325								
Cadmium Plated Steel	PANS6350	.350	Material Thickness Range >	.080 - .123	.130 - .173	.180 - .223	.230 - .273	.3280 - .323	.330 - .373
Stainless Steel	PANSSS6350								
Cadmium Plated Steel	PANS6375	.375	Material Thickness Range >	.055 - .098	.105 - .1048	.155 - .198	.205 - .248	.255 - .298	.305 - .348
Stainless Steel	PANSSS6375								
Cadmium Plated Steel	PANS6400	.400	Material Thickness Range >	.030 - .073	.080 - .123	.130 - .173	.180 - .223	.230 - .273	.280 - .323
Stainless Steel	PANSSS6400								
Cadmium Plated Steel	PANS6425	.425	Material Thickness Range >	.005 - .048	.055 - .098	.105 - .148	.155 - .198	.205 - .248	.255 - .298
Stainless Steel	PANSSS6425								